

## **Comparison / Differences between the SDS1000X and SDS1000X-E oscilloscope families**

**November 26, 2018**

The short list of differences between the X and the 2 channel XE (SDSs1202XE) is as follows:

- X has 50 ohm/ 1 MOhm selectable input impedance. XE only has 1 MOhm fixed. You will need a 50 ohm matching through adapter if you wish to connect to 50 Ohm circuits/minimize reflections.
- The X has a slightly larger display (8") vs. the XE (7")
- The XE has a faster digital platform with 1 Mpt FFT capability. The X has 16,384 pt depth for the FFT.

In addition, the SDS1xx4X-E scopes have additional differences:

- Onboard webpage control (standard)
- Bode Plot (standard.. requires SIGLENT SDG or SAG1021)
- External waveform/function generator (SAG1021 and SDS1000X-E-FG license Optional)
- WiFi control (TL-WN725N and SDS1000X-E-WiFi license Optional)



### **North American Headquarters**

SIGLENT Technologies NA  
6557 Cochran Rd Solon, Ohio 44139  
Tel: 440-398-5800  
Toll Free:877-515-5551  
Fax: 440-399-1211  
[info@siglent.com](mailto:info@siglent.com)  
[www.siglentamerica.com/](http://www.siglentamerica.com/)

### **European Sales Offices**

SIGLENT TECHNOLOGIES GERMANY GmbH  
Staetzlinger Str. 70  
86165 Augsburg, Germany  
Tel: +49(0)-821-666 0 111 0  
Fax: +49(0)-821-666 0 111 22  
[info-eu@siglent.com](mailto:info-eu@siglent.com)  
[www.siglenteu.com](http://www.siglenteu.com)

### **Asian Headquarters**

SIGLENT TECHNOLOGIES CO., LTD.  
Blog No.4 & No.5, Antongda Industrial Zone,  
3rd Liuxian Road, Bao'an District,  
Shenzhen, 518101, China.  
Tel:+ 86 755 3661 5186  
Fax:+ 86 755 3359 1582  
[sales@siglent.com](mailto:sales@siglent.com)  
[www.siglent.com/ens](http://www.siglent.com/ens)