

SVA1000X Firmware Revision History

Version	Revision
V3.2.2.4.0R2 2021/2/09	Notice: This firmware must be upgraded from V2.1.1.1.12a or later. If your SVA1000X has an earlier version, please update to V2.1.1.1.12a first and then proceed to update to the latest version. <ul style="list-style-type: none"> • This version can not be rolled back • Fix the VNA option license error on some SVA1015X and SVA1075X units
V3.2.2.4.0 2021/1/15	Notice: This firmware must be upgraded from V2.1.1.1.12a or later. If your SVA1000X has an earlier version, please update to V2.1.1.1.12a first and then proceed to update to the latest version. <ul style="list-style-type: none"> • This version can not be rolled back • Fix TG switch error at small RBW • Fix Help and Limit file lost when Factory reset • Fix Auto open delay unit error in VNA mode • Fix CNR calc error when no peak found • Fix OBW result overflow • Fix Harmonic calc error at 100Hz RBW • Fix Reflection Open+Short calibration action • Fix spectrum amplitude error in DMA mode • Optimize EMI .csv file content to all signal list • Optimize EMI peak search • Optimize Auto cal process • Add Peak search to Spectrum in DMA mode
V3.2.2.3.3R1 2020/12/01	Notice: This firmware must be upgraded from V2.1.1.1.12a or later. If your SVA1000X has an earlier version, please update to V2.1.1.1.12a first and then proceed to update to the latest version. <p>New Functionality:</p> <ul style="list-style-type: none"> • Add EMI filter in SA for EMI option <p>Solved Issues:</p> <ul style="list-style-type: none"> • Optimize the TG flatness and control procedure • Optimize Help • Fix Correction, .csv file, add peak numbers to 20 in EMI mode • Fix ADC overload warning error, and time unit error in Calibration in VNA Mode • Fix amplitude error in DMA Mode <p>Fix upgrade failure issue</p>
V3.2.2.3.2 2020/09/09	Notice: This firmware must be upgraded from V2.1.1.1.12a or later. If your SVA1000X has an earlier version, please update to V2.1.1.1.12a first and then proceed to update to the latest version.

Version	Revision
	<p>New Functionality:</p> <ul style="list-style-type: none"> • Add user defined VNA calibration kits • Add VNA 0 span calibration <p>Solved Issues:</p> <ul style="list-style-type: none"> • Fix avg power bug in EMI Mode • Fix amplitude bug in AMA Mode • Fix peak search bug in SCPI command
V2.2.1.2.8 2020/07/20	<p>Notice:</p> <p>This firmware must be upgraded from V2.1.1.1.12a or later. If your SVA1000X has an earlier version, please update to V2.1.1.1.12a first and then proceed to update to the latest version.</p> <p>New Functionality:</p> <ul style="list-style-type: none"> • Update EMI option to a new EMI measurement mode • Added more VNA calibration kits with N/3.5mm type connectors to 4.5G/9.0GHz • Added *.CSA file type to store instrument setup and calibration data in one file for easy recall and use of a saved state. • Update user calibration data format. <p>CAUTION: User calibration data taken with previous firmware revisions will no longer be compatible with the instrument after upgrading to V2.8. You will have to store new user calibration files if you update the instrument.</p> <ul style="list-style-type: none"> • VNA Port 1 output power and Port2 input Att adjustable <p>Improvements:</p> <ul style="list-style-type: none"> • Improve TG output harmonic performance • Update Help file <p>Solved Issues:</p> <ul style="list-style-type: none"> • Fix some ADC overload warning • Fix Ch Power calculation bug in small span
V2.2.1.2.7 2020/05/12	<p>Notice:</p> <p>This firmware must be upgraded from V2.1.1.1.12a or later. If your SVA1000X has an earlier version, please update to V2.1.1.1.12a first and then proceed to update to the latest version.</p> <p>New Functionality:</p> <ul style="list-style-type: none"> • Add Limit mask offset in SA mode • Frequency LOG scale in VNA mode • Add OPEN、SHOT、enhanced response in VNA mode • Add 85033D/E Cal kit in VNA mode • Save/recall .cal file in VNA mode

Version	Revision
	<ul style="list-style-type: none"> • Port 1 power (TG) adjustable in VNA mode • Zero span in VNA mode <p>Improvements:</p> <ul style="list-style-type: none"> • Smooth the glitch in Phase format in VNA mode <p>Solved Issues:</p> <ul style="list-style-type: none"> • Fixed AM and FM symbol rate error, Lpf coefficient error, in AMA mode • Fixed Filter bandwidth error in DMA mode • Fixed Freq counter error in SA mode • Fixed Harmonic error in SA mode • Help Display error
V2.2.1.2.5 2019/11/11	<p>Notice: This firmware must be upgraded from V2.1.1.1.12a or later. If your SVA1000X has an earlier version, please update to V2.1.1.1.12a first and then proceed to update to the latest version.</p> <p>Improvements:</p> <ul style="list-style-type: none"> • Optimize trace, marker, signal track, TG normalization in SA Mode • Optimize calibration flow, calibration algorithm and sweep speed in VNA Mode • Optimize web server UI <p>Solved Issues:</p> <ul style="list-style-type: none"> • Fixed video trigger fail, errors in Harmonic measurement in SA Mode • Fixed admittance error, port extensions error in VNA Mode • Fixed spectrum amplitude error, meas error, waveform discontinue in MA Mode • Fixed English help, system message
V2.2.1.2.2 2019/8/1	<p>Notice: This firmware must be upgraded from V2.1.1.1.12a or later. If your SVA1000X has an earlier version, please update to V2.1.1.1.12a first and then proceed to update to the latest version.</p> <p>New Functionality:</p> <ul style="list-style-type: none"> • Add a spectrum view, marker for MA Mode • Add mode couple for center frequency • Add system message <p>Improvements:</p> <ul style="list-style-type: none"> • Optimize .sta file, trace interpolation for VNA Mode • Optimize PSK/QAM clock sync ability for MA Mode <p>Solved Issues:</p> <ul style="list-style-type: none"> • Fixed AVG, Math bug for VNA Mode

Version	Revision
	<ul style="list-style-type: none"> Fixed Date&Time set bug
V2.2.1.2.1 2019/6/1	<p>Notice: This firmware must be upgraded from V2.1.1.1.12a or later. If your SVA1000X has an earlier version, please update to V2.1.1.1.12a first and then proceed to update to the latest version.</p> <p>New Functionality:</p> <ul style="list-style-type: none"> Add CNR, Harmonic measurement in AMK options for SA Mode Add port extensions, user cal kit, new marker functions, correction switch, multi-traces and multi-format overlay display for VNA Mode Extend xQAM, MSK, xPSK modulation analysis in DMA option for MA Mode Add new marker functions, multi-traces and multi-format overlay display for MA Mode Add SCPI commands for VNA and MA Modes Add some system functions: Screen Annotation in Display menu, FTP server for file transfer <p>Improvements:</p> <ul style="list-style-type: none"> Optimize UI, refresh and response for all Modes Optimize SCPI commands for basic control, such as INIT, *OPC?, *ESR, Abort, etc. Optimize Log scale axes, Peak search, Auto tune, TG normalization for SA Mode Optimize S11 and S21 simultaneous measurement, calibration control, trace control and auto scale for VNA Mode Optimize some system functions: Power Saving, IP config <p>Solved Issues:</p> <ul style="list-style-type: none"> Fixed OBW Transmit Freq Error Fixed bugs during Mode switch
V2.1.1.1.13 2018/11/1	<p>New Functionality:</p> <ul style="list-style-type: none"> Screen saver for power saving VNC View only for web server VNA: .csv file for each format, Expand Phase for marker <p>Improvements:</p> <ul style="list-style-type: none"> VNA: Auto Scale, min Scale to 0.1 dB DTF: logistic scale for RL display <p>Solved Issues:</p> <ul style="list-style-type: none"> Invalid Demod time in FM Scale in TG Wrong units in Markers and peaks Boot or Mode start lock up Udisk display wrong files

Version	Revision
	<ul style="list-style-type: none">• SCPI command incompatible• Min span to 10kHz in AMK power measurement
V2.1.1.1.12a 2018/8/8	<ol style="list-style-type: none">1. Spectrum Analysis mode : Improved the stability of sweep and interface.2. VNA mode: fasten the VNA sweep speed; expand the minimum span from 10M to 10 kHz.3. Modulation Analysis mode: add trigger, optimize the modulation analysis algorithm.4. Add user port number selection for web server.