

Minimum pulse repetition rate frequency for EMI enabled analyzers

June 09, 2022

The EMI toolkit available for many SIGLENT spectrum analyzers, such as the SSA3X, 3X Plus, SVA, and X-R series, feature a Quasi-peak detector that was designed to CISPR-16 specifications, which include pulse repetition rates.

The EMI toolkit has been tested with pulse repetition rate minimum of 20 Hz, but has not been tested below this.

Increased error is expected and therefore it is not recommended for use below 20 Hz.



North American Headquarters

SIGLENT Technologies NA 6557 Cochran Rd Solon, Ohio 44139

Tel: 440-398-5800 Toll Free:877-515-5551 Fax: 440-399-1211 info@siglent.com

www.siglentamerica.com/

European Sales Offices

SIGLENT TECHNOLOGIES GERMANY GmbH Staetzlinger Str. 70 86165 Augsburg, Germany

Tel: +49(0)-821-666 0 111 0 Fax: +49(0)-821-666 0 111 22

info-eu@siglent.com www.siglenteu.com

Asian Headquarters

SIGLENT TECHNOLOGIES CO., LTD.
Blog No.4 & No.5, Antongda Industrial Zone,
3rd Liuxian Road, Bao'an District,
Shenzhen, 518101, China.
Tel:+ 86 755 3661 5186
Fax:+ 86 755 3359 1582

sales@siglent.com
www.siglent.com/ens