

SSG3000X Pulse Modulation Spec Clarification

June 15, 2022

The Pulse Modulation states:

Modulation frequency response	10 Hz~100 kHz	<3 dB (nom.)
Pulse modulation		
Modulation source	internal, external	
On/off ration	1 MHz <f<3.2 GHz	>70 dBc
Raise/fall time (10% / 90%)	10% to 90% of RF amplitude	<50 ns
Pulse repetition time	setting range	40 ns~300 s
Pulse generator		

The SSG3000X Pulse Modulation is functional from 9 kHz to 2.1/3.2 GHz. The specification of 1 MHz- 3.2 GHz is guaranteed (as shown). Operation from 9 kHz-1 MHz is not guaranteed.



North American Headquarters

SIGLENT Technologies NA
6557 Cochran Rd Solon, Ohio 44139
Tel: 440-398-5800
Toll Free: 877-515-5551
Fax: 440-399-1211
info@siglent.com
www.siglentamerica.com/

European Sales Offices

SIGLENT TECHNOLOGIES GERMANY GmbH
Staetzlinger Str. 70
86165 Augsburg, Germany
Tel: +49(0)-821-666 0 111 0
Fax: +49(0)-821-666 0 111 22
info-eu@siglent.com
www.siglenteu.com

Asian Headquarters

SIGLENT TECHNOLOGIES CO., LTD.
Blog No.4 & No.5, Antongda Industrial Zone,
3rd Liuxian Road, Bao'an District,
Shenzhen, 518101, China.
Tel: + 86 755 3661 5186
Fax: + 86 755 3359 1582
sales@siglent.com
www.siglent.com/ens